Diesel Fuel Additive

Technical Data Sheet (TDS)

Areas of Use

- It prevents gelling and freezing in fuel. Ensures easier engine running in cold.
- Provides better combustion in fuel. Increases engine power and saves money. Clears residues, reduces power loss on motor.
- Reduces maintenance costs and exhaust fumes and contamination.

Directions for Use

- For 40-60 litres of fuel one Diesel Fuel Additive is mixed in fuel and used.
- Using it for every fuel consumption helps keep your engine maintained and clean.

Packaging Specifications

Size	Carton Dimensions	Pcs / Carton	Per Pallet
300 ML	360×230×220 mm	24 pcs	2184 pcs

AUTO CHER OTO BAKIM LİMİTED ŞİRKETİ · İçerenköy, Çetinkaya Sk. No:17, 34752 Ataşehir / Istanbul, Türkiye
Tel: +90 216 575 00 84 · Mobile / WhatsApp: +90 533 818 42 32 · info@autocher.com.tr · autocher.com.tr

Physical and Chemical Properties

Physical state	**Liquid**
Odour	**Characteristic**
pH	**Not applicable**
Melting point / Freezing point	**Not applicable**
Boiling point / Boiling interval	**Not applicable**
Flash point	**11,7- 12 °C**
Evaporation rate	**Not applicable**
Flammability	**Not applicable**
Upper/lower limits for flammability or explosion	**Not applicable**
Vapour pressure	**Not applicable**
Vapour density	**Not applicable**
Relative Density	**0,80-0,81 g/ml**
Solubility in water	**insoluble in water**
Log Pow (log octanol/water partition coefficient)	**Not applicable**
Auto-ignition temperature	**Not applicable**
Decomposition temperature	**Not applicable**
Fluidity	**Not applicable**
Explosive / oxidizing property	**Risk of explosion at temperatures above 50°C**
Viscosity	**Not applicable**

Consumer Information

Hazard Statements (H)

- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements (P)

Prevention

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
- P242 Use non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P261 Avoid breathing dust/fume/gas/mist/vapours/ spray.

- P264 Wash thoroughly with water after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response

- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
- P302+P352 IF ON SKIN: Wash with plenty of water.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P332+P313 If skin irritation occurs: Get medical advice/ attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P312 Call a POISON CENTER/doctor/if you feel unwell.
- P331 Do NOT induce vomiting.
- P362 Take off contaminated clothing.
- P370+P378 In case of fire: Use dry chemical powder to extinguish.
- P391 Collect spillage.

Storage

- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.

Disposal

- P501 Dispose of contents/container to.