Multipurpose Care Spray

Technical Data Sheet (TDS)

Areas of Use

- The multipurpose product for household using, hobby, workshop, vehicle and industry.
- For hinges, rollers, locks, bolts, switches, handles, and much more.
- Lubricates, cleans, loosens, protects and preserves.
- Keeps moving parts rapidly moving.
- Reaches even the most hidden lubrication points thanks to its excellent penetration properties.
- Loosens stubbornly rusted and burnt-on screws quickly.
- Infiltrates and removes dirt and stubborn oil and grease residues.
- Provides protection against rust and corrosion and protects chrome parts.
- It removes water and moisture.
- It is used as an excellent water repellent in automotive and shipbuilding industries, electrical contacts, engines where water and moisture are not desired.

Directions for Use

- Shake well before use.
- The box can be used upside down with a special valve system.
- Attach the red tube to the actuator.
- Product is applied to the surface then wait a couple of seconds for well penetration.
- It contains ozone friendly ingredients that does not harm the environment.

Physical and Chemical Properties

Appearance	**Aerosol**
Colour	**not available**
Odour	**Characteristic**
Melting point / freezing point	**not available**
Initial boiling point	**not available**
Flammability	**not available**
Explosive properties	**There is a risk of explosion at temperatures above 50 °C**
Lower explosive limit	**not available**
Upper explosive limit	**not available**
Flash point	**not available**
Auto-ignition temperature	**not available**
Decomposition temperature	**not available**
pH	**not available**
Kinematic viscosity	**not available**
Solubility	**Insoluble in water**
Partition coefficient: n-octanol/water	**not available**
Vapour pressure	**not available**
Density and/or relative density	**0.68-0.70 g/mL**
Relative vapour density	**not available**
Particle characteristics	**not applicable**

Consumer Information

Hazard Statements (H)

- H222 Extremely flammable aerosol.
- H229 Pressurised container: may burst if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.
- H350 May cause cancer.
- H411 Toxic to aquatic life with long-lasting effects.
- Restricted to professional users.

Precautionary Statements (P)

Prevention

- P201 Obtain special instructions before use.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.

- P251 Do not pierce or burn, even after use.

Response

- P331 Do NOT induce vomiting.

Storage

- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.