Stop Leak Radiator

Technical Data Sheet (TDS)

Areas of Use

- It is a sealing product to stop small leaks in the radiator, cooling and heating system, and head gaskets.
- It is compatible with all antifreezes and coolants.
- It is formulated to avoid the clogging of radiator waterways and temperature sensors.
- Protects Engine Cooling Systems.
- Inhibits rust and corrosion.
- Lubricates water pump seal.
- Helps control electrolysis.

Directions for Use

- For best results, use 1 package for vehicles with a cooling system volume of 2 to 18 liters. For vehicles with more than 18 liters, use 2 to 3 packages.

AUTO CHER OTO BAKIM LİMİTED ŞİRKETİ · İçerenköy, Çetinkaya Sk. No:17, 34752 Ataşehir / Istanbul, Türkiye
Tel: +90 216 575 00 84 · Mobile / WhatsApp: +90 533 818 42 32 · info@autocher.com.tr · autocher.com.tr

Physical and Chemical Properties

Appearance	**Aerosol**
Colour	**blue**
Odour	**characteristic**
Melting point / freezing point	**not available**
Initial boiling point	**not available**
Flammability	**not available**
Lower explosive limit	**not available**
Upper explosive limit	**not available**
Flash point	**not available**
Auto-ignition temperature	**not available**
Decomposition temperature	**not available**
pH	**12-13**
Kinematic viscosity	**not available**
Solubility	**not available**
Partition coefficient: n-octanol/water	**not available**
Vapour pressure	**not available**
Density and/or relative density	**1-1,1 g/ml**
Relative vapour density	**not available**
Particle characteristics	**not applicable**

Consumer Information

Hazard Statements (H)

- H373 May cause damage to organs through prolonged or repeated exposure.
- H319 Causes serious eye irritation.
- H315 Causes skin irritation.

Precautionary Statements (P)

- P280 Wear protective gloves / eye protection / face protection.
- P337+P313 If eye irritation persists: Get medical advice / attention.
- P264 Wash hands thoroughly after handling.