Rust Remover Spray MoS2

Technical Data Sheet (TDS)

Areas of Use

- Can be used on all metal surfaces affected by rust caused by water and humidity.
- Suitable for stuck nuts and bolts, hand tools, hunting equipment, bicycle and motorcycle parts, door and wardrobe hinges and all other metal surfaces.
- Forms a film layer after removes the rust.
- Helps to delay the rusting.
- Not harmful to plastic components.

Directions for Use

- Shake the can well before use.
- Attach the red pipe to the actuator.
- Spray it by a distance of 10-20 cm.
- Spray to rusted areas.
- Wait until penetrated.
- Dry and wipe the parts in a well-ventilated place or outdoors.
- Apply several times in case of heavy rust.
- Contains ozone friendly propellant.

AUTO CHER OTO BAKIM LİMİTED ŞİRKETİ · İçerenköy, Çetinkaya Sk. No:17, 34752 Ataşehir / Istanbul, Türkiye
Tel: +90 216 575 00 84 · Mobile / WhatsApp: +90 533 818 42 32 · info@autocher.com.tr · autocher.com.tr

Physical and Chemical Properties

Appearance	**Aerosol**
Colour	**not available**
Odour	**Characteristic**
Melting point / freezing point	**not available**
Initial boiling point	**not available**
Flammability	**not available**
Lower explosive limit	**not available**
Upper explosive limit	**not available**
Flash point	**not available**
Auto-ignition temperature	**not available**
Decomposition temperature	**not available**
pH	**not available**
Kinematic viscosity	**not available**
Solubility	**Insoluble in water**
Partition coefficient: n-octanol/water	**not available**
Vapour pressure	**not available**
Density and/or relative density	**not available**
Relative vapour density	**not available**
Particle characteristics	**not applicable**
Explosive properties	**There is a risk of explosion at temperatures above 50°C**

Consumer Information

Hazard Statements (H)

- H223 Flammable aerosol.
- H229 Pressurised container: may burst if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.
- H350 May cause cancer.
- H411 Toxic to aquatic life with long lasting effects.
- Restricted to professional users.

Precautionary Statements (P)

Prevention

- P201 Obtain special instructions before use.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.

- P251 Do not pierce or burn, even after use.

Response

- P331 Do NOT induce vomiting.

Storage

- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F.